

S SERIES: SINGLE-PHASE INDUSTRIAL VACUUMS

INDUSTRIAL VACUUM SOLUTIONS



S2 & S3: NEXT GENERATION OF INDUSTRIAL VACUUMS

The S2 and S3 single-phase industrial vacuums are designed to meet a wide range of industrial cleaning challenges. Available in a variety of configurations, they feature strong, solid construction and cutting-edge innovations.

» Simplify Maintenance & Reduce Downtime

- Modular design for easy modifications and servicing
- Electronic keypad with LED indicators to monitor filter performance
- Optional liquid and solid level LED sensors (26 gal. models only) that automatically shut off the machine when maximum capacity is reached

» Decrease Dust Exposure

- Optional upstream HEPA filtration ensures 99.995% of particles are retained, down to and including 0.18 microns
- Available with polyliner adapter kit for safer and easier disposal of collected material

» Industries

Bakeries Paper/Corrugated
Firing Ranges Powder Coating
Food Processing Printing
Packaging Textiles
Metalworking Woodworking







Technical Features	S2N1		S2N6	
Collection Type	Dry		Dry	
Voltage @ 60 Hz	120 V		120 V	
Type of Power	1-phase		1-phase	
Power @ 60 Hz	2.68 HP (2000 W)		2.15 HP (1600 W)	
Current, max.	14.5 amps		11.5 amps	
Airflow, max.	198 CFM (5607 L/min)		180 CFM (5097 L/min)	
Waterlift, max.	83.1 in. H ₂ O (2111 mm H ₂ O)	71.5 in. H ₂ O (1816 mm H ₂ O)	
Container Capacity	13 gal. (50 L)	26 gal. (100 L)	13 gal. (50 L)	26 gal. (100 L)
Main Filter Area, standard	20.99 ft. ² (1.95 m ²)		20.99 ft.² (1.95 m²)	
Main Filter Area, oversized	31.22 ft.² (2.9 m²)		31.22 ft.² (2.9 m²)	
HEPA Filter Area, upstream	37.7 ft. ² (3.5 m ²)		37.7 ft. ² (3.5 m ²)	
HEPA Filter Efficiency	99.995% @ 0.18 microns		99.995% @ 0.18 microns	
Machine Inlet Diameter	70	mm	70 mm	
Dimensions (L x W x H)	31.5 in. x 23.6 in. x 51.2 in. (800 mm x 600 mm x 1300 mm)	31.5 in. x 23.6 in. x 62.2 in. (800 mm x 600 mm x 1580 mm)	31.5 in. x 23.6 in. x 51.2 in. (800 mm x 600 mm x 1300 mm)	31.5 in. x 23.6 in. x 62.2 in. (800 mm x 600 mm x 1580 mm)
Weight, machine only	139 lb. (63 kg)	140 lb. (63 kg)	139 lb. (63 kg)	140 lb. (63 kg)
Cord Length	30 ft. (10 m)		30 ft. (10 m)	
Protection Class	IP44		IP44	
Sound Pressure Level @ 3'3"	70 dB(A)		70 dB(A)	

ENDLESS POSSIBILITIES













\$3	N1	S3N2		
Dry (Wet	t Option)	Dry (Wet Option)		
12	0 V	220 V		
1-pl	nase	1-phase		
3.22 HP ((2400 W)	4.02 HP (3000 W)		
15.8	amps	13 amps		
270 CFM (7	7646 L/min)	314 CFM (8891 L/min)		
71.5 in. H ₂ O (1	1816 mm H ₂ O)	90 in. H ₂ O (2286 mm H ₂ O)		
13 gal. (50 L)	26 gal. (100 L)	13 gal. (50 L)	26 gal. (100 L)	
20.99 ft. ²	(1.95 m²)	20.99 ft. ² (1.95 m ²)		
31.22 ft.	² (2.9 m ²)	31.22 ft. ² (2.9 m ²)		
37.7 ft. ²	(3.5 m ²)	37.7 ft. ² (3.5 m ²)		
99.995% @	0.18 microns	99.995% @ 0.18 microns		
70	mm	70 mm		
31.5 in. x 23.6 in. x 51.2 in. (800 mm x 600 mm x 1300 mm)	31.5 in. x 23.6 in. x 62.2 in. (800 mm x 600 mm x 1580 mm)	31.5 in. x 23.6 in. x 51.2 in. (800 mm x 600 mm x 1300 mm)	31.5 in. x 23.6 in. x 62.2 in. (800 mm x 600 mm x 1580 mm)	
150 lb. (68 kg)	157 lb. (71 kg)	150 lb. (68 kg)	157 lb. (71 kg)	
30 ft.	(10 m)	30 ft. (10 m)		
IP ₄	14	IP44		
71 d	B(A)	71 dB(A)		

Safe Choice Commitment

At Nilfisk Industrial Vacuums we understand that you face many risks each day, just by operating your business. That is why Nilfisk is dedicated to helping you make smart choices to keep your facility and your workers safe. Our team of experts is ready to tackle any cleaning challenge — because in a world full of risk, you have to make safe choices.

We are committed to being that safe choice. To learn more, visit nilfiskindustrialvacuums.com.





Nilfisk-Advance, Inc. Industrial Vacuum Division 740 Hemlock Rd., Suite 100 Morgantown, PA 19543 United States (800) 645-3475

www.nilfiskindustrialvacuums.com questions@nilfisk.com