A Spotless Reputation... With a Guarantee to Prove It!

We've earned our solid reputation by consistently producing top-quality vacuums and offering the industry's most complete selection of vacuum filtration options, attachments, and accessories.

We back all of our products with our industryleading two-year warranty. Nilfisk Industrial Vacuums empowers you with complete buying confidence.


For a list of major customers in your industry, please contact our headquarters or your local representative.

Visit www.NilfiskIndustrialVacuums.com for more information or call 800-NILFISK for our full line catalog.



T26 Plus - T48 Plus - T63 Plus Industrial Vacuums







Nilfisk Industrial Vacuum Division

740 Hemlock Road Suite 100 Morgantown, PA 19543 Tel. 800.645.3475 www.nilfiskindustrialvacuums.com questions@nilfisk.com







The Ultimate Cleaning Muscle

Nilfisk CFM T Plus Series: Three-phase Industrial Vacuums



Introducing Nilfisk CFM's new generation of three-phase industrial vacuums, the T Plus series. Comprised of the T26 Plus, T48 Plus and T63 Plus, these machines allow customers an opportunity to have a "tailor made" industrial vacuum cleaner. With a smarter design, the new T Plus Series can easily accept a wide range of options and upgrades. These vacuums efficiently collect a variety of materials, including toxic, hazardous, and nuisance dust, debris, and liquids. Every feature is engineered to make daily cleaning in production areas and process manufacturing fast and hassle-free.

- Lightweight and highly maneuverable, the T Plus series vacuums feature rear swiveling wheels with locking brakes.
- A unique release lever lowers the wheeled collection container and acts as a handle for fast and easy disposal of collected debris.
- Low noise operation, the T Plus vacuums are quiet, increasing worker safety and comfort.
- Possible electrical upgrades include automatic filter cleaning, wet or dry level sensors or remote start/stop.

Description	Units	T26 Plus	T48 Plus	T63 Plus
Voltage @ 60Hz	Volts	220 / 460 / 575	220 / 460 / 575	220 / 460 / 575
Power, max	kW	2.6	4.8	6.3
Current Draw, max	amps	11.4 / 6.0 / 4.6	25.0 / 10.4 / 7.6	25.0 / 13.3 / 10.4
Waterlift, controlled	Inches H2O	82.6	140.5	82.6
Airflow, max	cfm	222	222	345
Filter Area, main	Square ft.	21	21	37.7
Filter Area, HEPA (upstream)	Square ft.	37.7	37.7	37.7
Sound Pressure @ 1.5m (ISO 3744)	dB(A)	67	71	71
Protection Class	IP	55	55	55
Insulation Class	Class	F	F	F
Tank Capacity	Gallons	26	26	26
Machine Inlet	mm	70	70	70
Cord Length	Feet	30	30	30
Filter Efficiency, HEPA	MPPS tested	99.995% @ 0.18 microns	99.995% @ 0.18 microns	99.995% @ 0.18 microns
Dimensions (L x W x H)	inches	50.8 x 23.6 x 60.6	50.8 x 23.6 x 60.6	50.8 x 23.6 x 64.6
Weight, machine only	lbs	303	356	367

* Specifications are subject to change without notice.

Construction: The T Plus series is constructed of a heavy duty steel frame, stainless steel collection container and polypropylene lid.

Filtration systems: The T Plus series come standard with a high efficiency main filter and upstream HEPA filter which ensures that 99.995% of particles are retained, down to and including 0.18 microns in size. This exceeds HEPA filter standards. An optional downstream exhaust ULPA filter or activated carbon filter is available.

Filter cleaning systems: The T Plus series machines come standard with a manual filter shaker that quickly removes caked on dust from the filter's surface, maintaining the vacuum's maximum suction power and improving productivity.

Collection options: For easy cleaning and improved sanitation, the T26 Plus, T48 Plus and T63 Plus comes standard with a 26-gallon stainless steel collection container. Also available with a dust bag or Longopac® Collection System for safe disposal of toxic and hazardous material.















