

EZ 8015/9015/P 9015

Single-Clip Machine



CLIP LINE[®]
Easy



innovative · reliable · leading

poly-clip[®]
SYSTEM

- Horizontal Single-Clip Machine
- For closure of very heavy and large bags, sacks and nets
- Tamper-proof originality closure
- Made of 100% corrosion-resistant stainless steel and industrial plastic

Applications

The horizontal Easy Clip Line® machines EZ 8015/9015/P 9015 safely package substances in granular, powder, liquid or solid form. They are also suitable for dust-free filling by nozzles from above. Possible filling goods in the food sector are, e.g., poultry, fruit or vegetables, and in the non-food sector, e.g. chemical substances such as granules, easily flammable substances, small parts, carpets, blankets, sand, and many other products.

Advantages

- Simple operation
- Quick, tight and reliable closure with uniform packaging
- Safe closing of the separator gate due to two-handed operation
- Hygiene due to stainless steel and industrial plastic with simple cleaning
- Low maintenance effort and wear because there are only few movable parts
- Also suitable for installation in packaging plants
- Processes high quality clips in stick version, certified according to ISO 22000 with compliance of HACCP requirements; plastic clips in addition according to FDA

EZ P 9015

The EZ P 9015 is specially designed for use of plastic clips and is suitable, in particular, for use of metal detectors and for filling of chemical/pharmaceu-



Version EZ P 9015 processes plastic clips.

tical substances, in particular corrosive, toxic and easily flammable substances. Particularly suited for use in locations exposed to the danger of explosions (explosion-proof devices) and clean rooms.

Optional equipment

- EZ 8015/9015 with pneumatic bottom knife for shorter product tails
- Easy to move and position due to trolley with fixable wheels to ensure good hold
- Bracket for mounting on rod at diameters of 35-48 mm
- Pressure reducer with filter

Function and operation

The clippers EZ 8015/9015/P 9015 operate pneumatically. The filled bags are automatically gathered by insertion into the clip guide slot and closing the separator gate by safe two-handed operation. At the same time, the clipping process is initiated and the product is reliably packaged.

Technical data

	EZ 80/9015	P 9015
Width (mm):	ca. 500	
Depth (mm):	ca. 800	
Height (mm):	ca. 850-910	
Weight (kg):	36	34
Compressed air:	5-7 bar/0.5-0.7 MPa	
Air consumption (NL/cycle):	12.3	7.9
Suitable clip sizes:		
EZ 8015:	S 844/848/854/860	
EZ 9015:	S 978/988/998	
EZ P 9015:	P 911/939/961	