



# PRESSURE CALIBRATOR TS 92.4...

# ...for precise pressure calibration



The pressure calibrator is used for precise monitoring and adjustment of pressure gauges and transmitters. It is equipped with a precision manometer. A fine adjusting screw and a valve complete this portable device.

#### **BENEFITS:**

- Precise pressure generation
- Digital precision manometer
- Integrated pressure pump
- Easy operation
- Fine adjusting screw
- Portable
- Battery operated
- Three versions with several pressure ranges

#### **OPERATION:**

The pressure gauge to be checked is connected directly to the quick coupling of the calibrator. After closing the valve, the pressure can be increased by the hand pump and decreased by the valve. Small changes can be made by the fine adjusting screw.

#### **TECHNICAL DATA:**

#### Low pressure calibrator

 Air pump:
 up to 10 bar / 145psi

 Vacuum pump:
 down to -850 mbar / -12.3psi

 Pressure range:
 -1...2 bar / -14.5...29psi

 -1...10 bar / -14.5...145psi

#### Medium pressure calibrator

Integrated hand pump

Pressure range: -1...10 bar / -14.5...145psi -1...20 bar / -14.5...290psi -1...25 bar / -14.5...362.5psi

#### High pressure calibrator

#### Pre-compression pump

Screw compressor for pressurizing and fine adjustment Oil reservoir

Pressure range: 0...200 bars / 0...2900psi 0...350 bars / 0...5075psi 0...700 bars / 0...10150psi

## All calibrators

Accuracy: Resolution: Battery life: Displays: Memory: Interface: 0.1% FS, within 0...50°C / 32...122°F 7400 steps (0.014% FS) approx. ½ year, permanent operation Pressure, temperature, time, unit 946 readings (optional 8114) RS 232

#### Steinfurth, Inc.

305 Etowah Trace • Suite 102 • Fayetteville, GA 30214 Phone: (678) 674 1096 • Fax: (678) 674 1097 e-mail: info@steinfurth.com Internet: www.steinfurth.com

### Steinfurth Mess-Systeme GmbH (Germany)

Bonifaciusring 15 • D-45309 Essen Phone: +49 (201) 85517-0 • Fax: +49 (201) 85517-20 e-mail: info@steinfurth.de Internet: www.steinfurth.de