

150# Flanged Ball Valves

NEW**Applications:**

- suitable for air, water, oil and gas

Features:

- product approvals include: LP gas shut-off valves, flammable liquid shut-off valves, gas shut-off valves, compressed gas shut-off valves, and anhydrous ammonia shut-off valves
- Body: ASTM A216 WCB
- RPTFE seat
- vacuum service to 29 inches of Hg
- pressure rating: **150 PSIG** saturated steam
- temperature up to **400°F**
- PSI rating up to **280 PSI**
- four point ISO 5211 mounting pad bolt pattern
- anti-static grounded ball and stem
- blow-out proof stem design
- bleed/drain port (cast) ½" NPT
- fire safe (graphite packing and seal)
- adjustable packing gland



Size	Port	Carbon Steel	
		Part #	Price/E
2"	full	FLBV200CS	\$1260.00
2½"	full	FLBV250CS	2125.00
3"	full	FLBV300CS	2205.00
4"	full	FLBV400CS	3370.00
6"	full	FLBV600CS	7642.00
8"	full	FLBV800CS	15526.00

Polypropylene Bolted Ball Valves

Features:

- pressure rating: ½" - 3" is rated to **125 PSI** at 70°F
4" is rated to **90 PSI** at 70°F
- chemically-resistant, reinforced polypropylene
- PTFE ball seat
- EPDM O-ring body seal, FKM O-ring stem seal
- 304 stainless steel nuts and bolts
- FDA approved material

4-bolt valve design

female NPT x female NPT

Size	Port	Polypropylene		Opt Qty
		Part #	Price/E	
½"	full	PVFP50	\$48.50	24
¾"	full	PVFP75	48.50	24
1"	full	PVFP100	56.50	24
1½"	full	PVFP150	72.25	24
1"	standard	PV100	48.50	24
2"	standard	PV200	70.00	24



Q

6-bolt valve design

female NPT x female NPT

Size	Port	Polypropylene		Opt Qty
		Part #	Price/E	
2"	full	PVFP200	\$102.00	12
3"	full	PVFP300	246.75	8
4"	full	PVFP400	520.00	4

