

723/706



SPRASOLVO®/RUSTSOLVO®

Description

Chesterton® 723 Sprasolvo* is a high quality, fast acting, penetrating oil which reaches deeply in and frees frozen nuts, bolts, and fittings without injury to the base metal.

Due to its excellent capillary action, 723 Sprasolvo will reach inaccessible places other penetrants will not touch. Breakaway torque is significantly reduced as the product penetrates every bit of rust, scale or corrosion and loosens tar, grease, dirt and deposits of carbon and graphite.

Most penetrating oils on the market today are designed for multiple functions- displacing moisture, protecting against corrosion, lubricating and finally, loosening rusted bolts. The result is a compromise product. Unlike these other products which claim to be all things to all users, 723 Sprasolvo was formulated to provide only one function; that of the best possible penetration. Use Chesterton 723 Sprasolvo when a true penetrating oil is needed.

Composition

Chesterton 723 Sprasolvo was formulated to optimize its singular function of penetration. Lubricants, moisture displacers and corrosion inhibitors are not added to the product

Typical Physical Properties	723/706	723 FG/706 FG
Form	Liquid	Liquid
Color	Blue	Clear
Odor	Petroleum	None
Specific Gravity	0,83	0,83
Flash Point	49°C (120°F)	62°C (144°F)

as these only decrease penetrating ability.** By providing the best penetration, second applications of the penetrant can be avoided and labor saved in replacing bolts that might otherwise have had to be removed with a torch.

723 Sprasolvo contains no acids or other chemicals injurious to base metals and paints. It flows freely under all weather conditions with a low surface tension that allows the product to creep into extremely long, microscopic spaces.

Handy aerosol cans of 723 Sprasolvo contain 95% usable product and utilize safe efficient carbon dioxide as propellant.

* Chesterton® 706 Rustsolvo® is the same fast acting penetrating oil in bulk form.

**Use Chesterton® 601 Chain Drive Pin & Bushing Lubricant when an excellent light lubricant is needed; use Chesterton® 775 Moisture Shield for a moisture displacing and corrosion inhibiting coating.

Applications

Use on plumbing, machinery, trucks, pipe lines, railroads, tractors, steam and gas fittings, valves, pumps, drilling utilities, auto shops, and ships. Use anywhere rust, tar, grease and dirt deposits on nuts and bolts prevent easy removal.

Features

- Singular Function
- Pin-point Jet Spray
- Extremely Low Surface Tension
- 723: NSF H2 - Registration number 133939
- 706: NSF H2 - Registration number 133942
- 723 FG: NSF H1 - Registration number 134006
- 706 FG: NSF H1 - Registration number 134005
- 723 FG/706 FG - Conforms to FDA Standard 21CFR 172.884, 178.3620, 178.3650

Benefits

- No compromise – Best possible penetration
- Creeps into microscopic spaces
- Can be used in federally inspected meat and poultry plants
- Directed exactly at needed spots

Directions

Apply 723 Sprasolvo® directly from handy aerosol dispenser. 706 Rustsolvo® can be applied using squirt oiler or oil can with extended spout. Apply evenly and allow a minute for deep penetration.

Safety

Before using these products or product, review the Material Safety Data Sheet (MSDS) or the appropriate safety sheet for your area.

Technical Data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W.CHESTERTON COMPANY DISCLAIMS ALL WARRANTIES EXPRESSED, OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE OR USE. LIABILITY, IF ANY, IS LIMITED TO PRODUCT REPLACEMENT ONLY.



860 Salem Street
Groveland, Massachusetts 01834 USA
Tel: (781) 438-7000 • FAX: (978) 469-6528
www.chesterton.com
© 2014 A.W. Chesterton Company.
® Registered trademark owned and licensed by
A.W. Chesterton Company in USA and other countries.

DISTRIBUTED BY:

FORM NO. 074280

REV. 12/14