


DETONATION SAFETY BARRIER F53 DEFLAGRATION VOLUME PROTECTION DEVICE F53



The deflagration volume protection device is ideal for protection of plants and equipment with a volume of max. 4.6 l.

Suitable as a detonation safety barrier ideal for mounting in small pipelines and to protect appliances, for example gas analysers.

Benefits

- compact design according to DIN EN ISO 16852
- offer security in case of deflagrations and stabile detonations
- applicable for almost all flammable gases and gas mixtures (not combined with oxygen)
- low life cycle costs
- may be mounted in any position / orientation
- compact size for easy, problem free installation
- designing and testing according to Directive 94/9/EC test report: PTB Ex 14-44012
- EC type-examination certificate PTB 14 ATEX 4003 X

Function and description

- the fitting protects against deflagrations and stabile detonations. This allows mounting into pipelines in any position / orientation, independent of distance to the potential source of ignition. The small and compact design of the flame arrester is for use in pipelines.

Approvals

Company certified according to ISO 9001 and ATEX 95 Directive 94/9/EC

Marking

Ex II G IIC
mounting position gS
(geschützte Seite / protected side)

Other models, options and accessories available upon request.


Application	Material	Standard gap width	Temperature	Volume	max. working pressure absolute	Connection	Order-No.
Deflagration volume protection device	Inlet fitting, Outlet fitting, housing 1.4305 / AISI 303	< 0.5 mm	max. 60 °C	max. 4.6 l	1.1 bar	Inlet F, G 1/4 Outlet M, M 12	145-250
Detonation safety barrier	O-ring 72 NBR 872 flame arrester 1.4404 / AISI 316L			–		1.5 bar	

DETONATION SAFETY BARRIER F53

DEFLAGRATION VOLUME PROTECTION DEVICE F53

F53
 Detonation safety barrier
 145-258

Flow diagram for air (20 °C / 68 °F)



Conversion factors:

Acetylene	x 1.04
Butane	x 0.68
Natural Gas	x 1.25
Methane	x 1.33
Propane	x 0.80
Oxygen	x 0.95
Town gas	x 1.54
Hydrogen	x 3.75

Flow diagram upon request (depend on the system requirements)

F53
 Deflagration volume
 protection device
 145-250