

FLASHBACK ARRESTOR 85-20



WITT Flashback Arrestors for reliable protection against dangerous reverse gas flow and flashbacks according to EN 730-1 / ISO 5175, UL 1357/1358. Every Arrestor 100% tested.



The best Flashback Arrestors in the world

- a large surface area flame arrestor **[FA]** of stainless steel construction extinguishes any dangerous flashback entering the device in any direction
- a temperature sensitive cut-off valve **[TV]** extinguishes sustained flashbacks long before the internal temperature of the arrestor reaches a dangerous level
- a spring loaded non-return valve **[NV]** prevents slow or sudden reverse gas flow from forming explosive mixtures in the gas supply

Operation / Usage

- Flashback Arrestors are used to protect gas cylinders and pipeline outlet points (hoses and any equipment) against dangerous reverse gas flow and flashbacks
- for pipeline outlets and single cylinders with high flows, for example, supply units for gas cutting machines
- WITT Flashback Arrestors may be mounted in any position/orientation
- only one piece of equipment may be connected to a single Flashback Arrestor
- the maximum ambient/working temperature is 158°F

Maintenance

- annual testing of the non-return valve, body leak tightness and flow capacity is recommended
- WITT is happy to supply special test equipment
- Flashback Arrestors are only to be serviced by the manufacturer

Approvals

Company certified according to ISO 9001

Other gases and connections available upon request

	Model
Safety devices	85-20
UL listed	UL 20110503-MH10017
Flame arrestor [FA]	X
Non-return valve [NV]	X
Temperature sensitive cut-off valve [TV]	X
Weight [oz]	51.15
Material	Brass (housing); Stainless steel (flame arrestor); Elastomer (seal)
Gases	max. working pressure [PSI]
	UL
Acetylene (A)	15
Natural gas (M)	50
LP (Propane)	50
Hydrogen (H)	50
MPS (Y)	50
Connections	Part No.
1/2" NPT / F*	149-003F-UL
3/4" NPT / F*	149-006F-UL
1" NPT / F*	149-017F-UL
Gases	max. working pressure [PSI]
	UL
Oxygen (O)	150
Connections	Part No.
1/2" NPT / F*	149-003O-UL
3/4" NPT / F*	149-006O-UL
1" NPT / F*	149-017O-UL

F* = two-sided female thread

FLASHBACK ARRESTOR 85-20



85-20

Conversion factors:

Acetylene	x 1.04
Butane	x 0.68
Natural Gas	x 1.25
Methane	x 1.33
LP (Propane)	x 0.80
Oxygen	x 0.95
Hydrogen	x 3.75
MPS	x 0.83

