

# BACKFIRE STOP – SRV for lance holder

## Backfire stop with temperature controlled cut-off valve and non-return valve

- protects against gas return and flashback
- combinable with WITT oxygen lancing equipment
- with copper sealing
- working temperature -10 °C – +60 °C (14 °F – 140 °F)


### Approvals

EN 9539, EN 560



Model	A Inlet connection male with cone according to EN 560 outlet connection female	Ø Lance [inch]	D [mm]	L [mm]	Weight [kg]	Flow rate [Nm³/h] P=10 bar	Max. working pressure [bar]	Order-No.
SRV 2.1	3/4"	up to 3/8"	36	90	0.39	250	Oxygen (O) 25.0	040996400
SRV 2.2	3/4"	1/2"	40	165	0.98	350		040686100
SRV 3	1"	3/4"	48	177	1.48	800		040686200
SRV 4	1.1/4"	1"	55	197	1.95	1,500		on request
SRV 5	1.1/2"	1.1/4"	65	215	2.67	2,500		on request

## Inlet-Reducer with copper-ring for Backfire stop – SRV



Connection EN 560		Order-No.
B Inlet	A Outlet	
G 3/8 M with cone	G 3/4 F	802339600K
G 1/2 M with cone	G 3/4 F	802339700K
G 3/4 M with cone	G 1 F	802418700K

Other connections available upon request