



“Speed, Flexibility, Dependable Performance”

ST-2602

Intermittent Side Seal Wrapper Texwrap quality and reliability

- Large capacity
- Flexible
- Film saving
- Easy to use

The ST-2602 is Texwrap's large size intermittent motion side seal machine designed to run larger products at moderate speed. With a capacity of 24" wide and 11.5" tall, the 2602 is versatile enough to accommodate a variety of product sizes and configurations.

The ST-2602 uses Texwrap's exclusive Versa Seal side seal to insure consistent, high quality seals across a wide range of film types. The TVS tightly clamps the film between parallel belts while a heating element seals and separates the film between them. The slightly diverging belts continue to clamp the film securely allowing the film seal to cure and, at the same time, assuring reliable scrap/trim separation. The belts on the TVS design also control film tension allowing consistent seals to be made using the absolute minimum film width possible saving money on every package.

Flexibility and ease-of-use are hallmarks of Texwrap design. With standard autospacing control, horizontal as well as vertical photoeyes, and the ability to precisely vary the conveyor speeds to relax the film between products, the ST-2602 can accommodate randomly fed or choke-spaced product and accurately separate them for reliable, consistent packages using the absolute minimum amount of film.



Made in USA

Distributed by:



TEXWRAP[®]
 525 Vossbrink Drive · Washington, MO 63090
 Ph (636)239-7424 · Fax (636) 239-7322
 sales@texwrap.com · www.texwrap.com

Features:

- Texwrap's exclusive Versa Seal side seal
- 30" hot knife cross seal with precision temperature control
- 24" wide infeed & exit conveyor
- 11.75" cross seal jaw opening
- Calibrated adjustments for product set-up
- Self contained scrap wind-up
- Horizontal and vertical photoeye controlled cross seal to provide automatic adjustment for bag length
- Pin perforator/brush air evacuation system
- Variable speed control with belt speed of 70 feet per minute
- Independent exit conveyor speed control
- Automatic autospace tuning feature adjusts machine to match upstream production
- Autospace for control of randomly spaced or choke fed products
- Allen Bradley PLC control
- Product set-up helper
- Adjustable film inverting head with controlled air bearing surfaces
- Autospace multipack ability

Specifications:

Maximum package size: 11"H x 24"W x infinite length

Minimum package size: 4"L x 2"W

Maximum film width: 54" single wound or 27" centerfolded
72" single wound or 36" centerfolded
(on optional, larger film unwind)

Electrical requirements: 240/208 Vac, 1 phase, 20/23 amps

Air requirements: 80 PSI

Machine controls: Allen Bradley

Maximum film speed: 70 FPM

Operator control panel: Swivel access, swivel mounted

