Models: P-, C-, CH-, CV-





Model P Jaw Sealers With Non-stick Covered Jaws: Sealing Polyethylene, Polypropylene, Similar Low Density Films and Bubble Pack Envelopes.

Model C Jaw Sealers With Flat or Serrated Jaws: Sealing Cellophane, Mylar, or Other High Temperature Films. Seal Bars Available with Horizontal or Vertical Serrated Jaws.



FEATURES

- 100F to 450F
- Heavy Duty All Aluminum Construction
- · Standard On/Off Switch on the Power Cord
- Serrated or Flat Jaws Available in Sizes Up to 24"
- Non-stick Cover (Included on Model P Only)
- Constant Heat with Adjustable Temperature Control, Range
 Standard Table Mounting with the Foot Pedal Bolted to the Floor
 - Foot Pedal Operation
 - · Seals All Types of Polyethylene, Polypropylene, Cellophane, Mylar, and other High Temp Bags

MODEL SPECS

JAW SIZE	8"	10"	12"	14"	16"	18"	24"
MODEL P	P-8	P-10	P-12	P-14	P-16	P-18	P-24
W/ NON-STICK COVER							
MODEL C	C-8	C-10	C-12	C-14	C-16	C-18	C-24
WITH FLAT SEAL	0 0	0.10	0 12		0 10	0 10	0 2 1
MODEL C HORIZONTAL	CH-8	CH-10	CH-12	CH-14	CH-16	CH-18	CH-24
SERRATED SEAL	CI I-0	011-10	OH-12	011-14	CH-10	CH-10	OI 1-24
MODEL C VERTICAL	CV-8	CV-10	CV-12	CV-14	CV-16	CV-18	CV-24
SERRATED SEAL	0.4-0	CV-10	GV-12	OV-14	CV-10	CV-10	GV-24
POWER	115 Volt, 5 Amps						
REQUIREMENT							
WATTAGE	600 Watts						
WEIGHT	10 lbs.	10 lbs.	11 lbs.	11 lbs.	12 lbs.	12 lbs.	14 lbs.

AVAILABLE OPTIONS

- Model 4 Jaw Sealer Stand- Foot Operated, Aluminum Stand, Compatible with All Jaw Sealer Models and Sizes. Stand Dimensions: 18" L, 10"W, 36" H, 20 lbs.
- Jaw Guards



Revised 2013